

Care and Maintenance

TPV and EPDM Surfaces



Care & Maintenance

Our goal is to supply a durable product that requires easy care and maintenance. Please follow these care and maintenance instructions to maximize the life of your rubber surfacing.

Care

Abrasive materials such as sand, gravel and rocks left on the surface will greatly shorten its life span.

Always keep the surfacing clean and free of all debris.

Typically cleaning the surface can be accomplished by using a leaf blower or broom.

Treat all stains with mild soap, a medium stream of water and soft bristle brush or broom. Avoid soaking the surface, American Rubber Surfacing is porous, water will pass through it and may create a muddy or soft sub base.

Avoid access water such as sprinklers or rain run-off from roofs.

Warning: The use of pressure washers and/or household cleaners will cause damage to the product and void its warranty.

Maintenance

In the first 12 months American Rubber Surfacing requires care as listed above and visual inspection for any damage. During year 2 between months 16 and 24 we recommend top coating the surfacing with a polyurethane binder. Although it is not required to coat the surfacing within these months it will lengthen the products lifespan and extend its warranty.

(end)

A division of
Hesscor, Inc.
1548 E. Main Street
Mesa, AZ 85203
p: 480-464-2700
f: 480-464-2705
e: info@hesscor.com
w: hesscor.com