

EPDM Colored Rubber Granule

Technical Data Sheet



Granule Size 1-3mm

Applications

Used for running track surfaces, playground wearing course and other various applications. This material can be spreader-applied, paved or mixed and troweled in place with the appropriate equipment in conjunction with an approved one or two component binder or coating.

Features

Virgin EPDM polymer (sulphur cured)

Free flowing out of the bag

Made from the highest quality raw EPDM materials available (Not "off-spec" EPDM)

Technical Information

Density kg/dm³: 1.59 +/- 0.04

Bulk density (loose) gr/l: approx. 660

Bulk density (compressed) gr/l: approx. 715

Colour stability Grey scale: 4-5

Fire class acc. EN9209-1: available on request

Raw material: EPDM rubber compound

Polymer content: 21% +/- 1%

Tensile strength N/mm²: approx. 6.0

Elongation at break %: approx. 650

Hardness Shore A 62: +/- 5

Storage and Handling

Keep material dry at all times and out of direct UV contact while in the plastic packaging. *Read the EPDM Colored Rubber Granule "Material Safety Data Sheet" before handling, or using this product.*

Notice

Avoid contact with oils, gasoline and similar products.

Packaging Form

Available in 40 bag pallets, in 55 pound (3 mil high strength "clear" plastic bags)

Colors Available

Red, Green, Blue, White, Grey, Eggshell, Beige, Bright Yellow, Yellow, Bright Green, Bright Blue, Dark Blue, Lilac, Bright Orange, Bright Red, Brown and Dark Grey

(end)

A division of
Hesscor, Inc.
1548 E. Main Street
Mesa, AZ 85203
p: 480-464-2700
f: 480-464-2705
e: info@hesscor.com
w: hesscor.com