

# EPDM Colored Rubber Granule

## Technical Data Sheet



### Granule Size 0.5-1.5mm

#### Applications

Used for running track surfaces, playground wearing course and other various applications. This material can be spreader-applied, paved or mixed and troweled in place with the appropriate equipment in conjunction with an approved one or two component binder or coating.

#### Features

Virgin EPDM polymer (sulphur cured)

Free flowing out of the bag

Made from the highest quality raw EPDM materials available (Not "off-spec" EPDM)

#### Technical Information

**Density kg/dm<sup>3</sup>:** 1.59 +/- 0.04

**Bulk density (loose) gr/l:** approx. 590

**Bulk density (compressed) gr/l:** approx. 670

**Colour stability Grey scale:** 4-5

**Fire class acc. EN9209-1:** available on request

**Raw material:** EPDM rubber compound

**Polymer content:** 21% +/- 1%

**Tensile strength N/mm<sup>2</sup>:** approx. 6.0

**Elongation at break %:** approx. 650

**Hardness Shore A 62:** +/- 5

#### Storage and Handling

Keep material dry at all times and out of direct UV contact while in the plastic packaging. *Read the EPDM Colored Rubber Granule "Material Safety Data Sheet" before handling, or using this product.*

#### Notice

Avoid contact with oils, gasoline and similar products.

#### Packaging Form

Available in 40 bag pallets, in 55 pound (3 mil high strength "clear" plastic bags)

#### Colors Available

Red, Green, Blue, White, Grey, Eggshell, Beige, Bright Yellow, Yellow, Bright Green, Bright Blue, Dark Blue, Lilac, Bright Orange, Bright Red, Brown and Dark Grey

A division of  
**Hesscor, Inc.**  
1548 E. Main Street  
Mesa, AZ 85203

p: 480-464-2700  
f: 480-464-2705  
e: [info@hesscor.com](mailto:info@hesscor.com)  
w: [hesscor.com](http://hesscor.com)

(end)